

SPYRO XSTREAM™

PROFESSIONAL GOLD DREDGE



ATM PROMINING™



PROFILE

Premium 8 Inch Double Sluice Concentration Dredge. For ultra professional gold miners, exploration companies and dredgers. Get productive. Never loose any Gold anymore.

CONTACT

Jl. Mampang Prapatan Raya No.
39. C5. 12790 Jakarta

- 021.7992077
- 0812.89401406
- www.tambang.id
- service@tambang.id
- Click for Coordinates

FREE CONSULTANCY

Special: Including Galvanized Tsunami Suction & Blaster Nozzle

APPLICATION

- | | |
|--------------------|-----------------------|
| Exploration | Underwater Ops |
| Massive Production | Professional Starters |
| Testpitting | River Gold Mining |
| Portabel Mining | Remote Locations |

SPECIFICATIONS

- | | |
|--------------------------------------------------------------|---------------------------------------------------------------------------|
| Motor | • Twin Motor. 2 x 15 HP. Special Modification. |
| Pumps | • 2 x 2/3 inch Venturi System Blower Jet. Special Modification. |
| Hose | • 8 inch x 6 m |
| Pontoon | • High Density Polyethylene - Rugged. Full Set. |
| Regulator | • Amscud |
| Air Hose | • 15 m |
| Suit & Mask | • Yes. Amscud / Cressi Diving Suit. 1 unit. |
| A.G.E.M.
<small>Anti Gold Escape Mechanism</small> | • Catchbucket on Primary Sluice End + Feeder Head Box + Auto-Reprocessing |
| Top Sluice | • Secondary Concentration Sluice for Fine Gold |

SLUICE SEGMENTATION

- | | |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| YES | Highly Segmented Sluice including ... <ul style="list-style-type: none">• SFS Sub Flow Gold Trap• Stream Equalizer• 2 Types of Slick Plates (10 & 6 mm)• 4 Hungarian Riffles• 4 EXP Plates• Grizzly Bars• 3 - 4 Types Miners Moss / Mats• Quick Clean Clamps• 260 x 85 x 35 cm Sluice Segment (Primary)• 230 x 58 x 15 cm Sluice Segment (Concentration) |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



IN LINE WITH ATM PROMINING DREDGE STANDARD 2018
EXCEEDING CLARKSON SLUICE STANDARDS

